Data Sheet

We make sure

FUJITSU COMPUTERS SIEMENS

MYRICA V32-1
LCD TV

Issue May 2005

Pages 2

Elegantly designed and brimming with high-end features, the 32" MYRICA LCD television is ready to meet today's and tomorrow's home entertainment demands. Sharp, lifelike images combines breath-taking sound to give you an unmatched viewing experience.
32" (81 cm) LCD screen with a wide viewing angle so everyone can enjoy the show HD ready: enjoy the quality of high-definition television. Resolution of an enormous 1366 x 768 pixels: TV never looked this good. Ultra-high 1000:1 contrast ensures brilliant clarity and detail. Plug-and-play connectivity: connecting your PC is effortless

- 32 inch wide screen LCD TFT display
- High resolution 1366 x 768 pixels
- 16.7 Mio colours
- Viewing angle 176°/ 176°
- High brightness 550 cd/m²
  and enormous contrast (1000:1)
- Multi norm TV tuner (PAL/SECAM)
- Various video inputs
- Teletext (256 pages)
- Plug and Play
  DDC 2B interface
- Immune to external electromagnetic fields
- Analogue (D-Sub) input and DVI-D with HDCP support
- 8 languages OSD menu
- Country specific warranty
- HD ready
- 8ms response time

8ms Response Time

HD ready

Visible screen diagonal	32 inch (81 cm) WXGA
Panel resolution	
pixels	1366 x 768
Picture size	603 x 336 mm
Brightness typical	550 cd/m²
Contrast typical	1000:1
Viewing angle typical	
Horizontal	176°
Vertical	176°
Response time g/g	8 ms
Options	
TV tuner	VHF/UHF/cable
Standard	B/G, D/K, I and L/L' (Multi Europe)
System	PAL / SECAM
Sound system	mono, stereo, dual tone
Teletext	256 pages (FLOF/TOP)
Video I/O	
TV-RF In	IEC-connect
DVI-D	with HDCP support
D-SUB	15pin
AV1 (In)	Component Video (YPbPr)
AV2 (In/Out)	21-pin Scart
AV3 (In/Out)	21-pin Scart
S-Video (In)	(4 pin Dim)
Composite video	RCA type
PC (Input)	
D-Sub	
DVI-D with HDCP support	
Horizontal frequency	31.15 – 64 kHz
Vertical frequency	56 – 75 Hz
Resolutions	1280 x 1024 60 Hz 1280 x 720 60 Hz 1024 x 768 60 - 75 Hz 800 x 600 56 - 75 Hz 640 x 480 60 - 75 Hz 640 x 350 70 Hz
Video	480i, 480p, 576i, 576p, 720p, 1080i with HDCP

Audio characteristics	
Volume control	digital
PC Audio (In)	3.5 mm stereo phone jack
6 x RCA (In)	Video, S-Video, Component
Earphone (Out)	3.5 mm stereo phone jack
Sub woofer (Out)	RCA pin
Sound output	8 W (L) + 8 W (R)

Electrical values	
External AC adapter	
Rated voltage	100-240 V
Frequency	50-60 Hz
Power draw	
Operating typical	155 W
Standby mode	< 5 W
Protection class	1
Temperatures/dimensions/weight	
Ambient temperature (to IEC721)	
Recommended range	15℃ to 35℃
Limit	5℃ to 35℃
Dimensions incl. stand (H x W x D)	580 x 792x 240 mm
Weight	approx. 19,3 (unpacked)
Reliability	
MTBF (demonstrated)	50000 h
Lifetime of backlight (brightness > 50 % of original brightness)	50000 h
Compliance with standards	
Product safety	EN60950 + IEC guide 112
Ergonomics	GS mark
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55013, EN55020B, EN55022/B, EN50024, 61000-3-2/-3)
Accessories	
Power cable (1.8 m)	for wall socket Euro-Schuko-Type CEE7 plug type IEC-320-C13
Remote control	incl. batteries (2x AAA)
User manual	multi language
Special features	
PIP (Picture-In-Picture)	
Automatic program search	
Order code	S26361-K1037-V170
EAN	4045827314332

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners.

Published by

Fujitsu Siemens Computers
http://www.fujitsu-siemens.com/

Company stamp

Copyright © Fujitsu Siemens Computers,09/2004